

## 7544 Group

### Clock Synchronous Serial I/O

---

#### 1. Abstract

The following article introduces and shows an application example of clock synchronous of serial I/O.

#### 2. Introduction

The explanation of this issue is applied to the following condition:  
Applicable MCU: 7544 Group

### 3. Contents

For clock synchronous serial I/O, the transmitter and the receiver use the same clock. Synchronizing with this clock, the transmit operation of the transmitter and the receive operation of the receiver are executed at the same time. If an internal clock is used as the operation clock, transfer is started by a write signal to the TB/RB.

#### 3.1 Data Transfer Rate

The synchronous clock frequency is calculated by the following formula;

- When the internal clock is selected (when baud rate generator is used)

$$\text{Synchronous clock frequency [Hz]} = \frac{f(X_{IN})}{\text{Division ratio}^{*1} \times (\text{BRG setting value}^{*2} + 1) \times 4}$$

Division ratio<sup>\*1</sup> : "1" or "4" is selected (set by bit 0 of serial I/O control register)

BRG setting value<sup>\*2</sup> : 0 to 255 (00<sub>16</sub> to FF<sub>16</sub>) is set

- When the external clock is selected

$$\text{Synchronous clock frequency [Hz]} = \text{Clock input to S}_{CLK} \text{ pin}$$

### 3.2 Clock Synchronous Serial I/O Setting Method

Figure 1 and Figure 2 show the setting method for the clock synchronous serial I/O.






Figure 1 Setting method for clock synchronous serial I/O (1)


Process 5: In order not to execute the no requested interrupt processing, set "0" (no requested) to the serial I/O transmit/receive interrupt request bit.



Process 6: When the interrupt is used, set "1" (interrupt enabled) to the serial I/O transmit/receive interrupt enable bit.



Process 7: Transmit/Receive of serial data (**Notes 1, 2**).



**Notes 1:** When data transmission is executed at the state that an external clock input is selected as the synchronous clock, set the transmit data while the SCLK is "H" state.  
**2:** When inputting the SRDY signal, set used pins to to the input mode before transmitting data.

Figure 2 Setting method for clock synchronous serial I/O (2)

### 3.3 Communication Using Clock Synchronous Serial I/O (Transmit/Receive)

**Outline** : 2-byte data is transmitted and received, using the clock synchronous serial I/O.  $\overline{\text{SRDY}}$  signal is used for communication control.

**Specifications** :

- The serial I/O (clock synchronous serial I/O selected ) is used.
- Synchronous clock frequency : 125 kHz;  $f(X_{\text{IN}}) = 4 \text{ MHz}$  divided by 32
- The receiver outputs the  $\overline{\text{SRDY}}$  signal at 2 ms intervals which the timer generates, and 2-byte data is transferred from the transmitter to the receiver.

Figure 3 shows a connection diagram, Figure 4 shows a timing chart, Figure 5 shows the control procedure of transmitter, and Figure 6 shows an example of control procedure of receiver.




Figure 3 Connection diagram




Figure 4 Timing chart




Figure 5 Control procedure of transmitter




Figure 6 Control procedure of receiver

#### 4. Sample Programming Code

##### [Reset Start ••• Main Routine Process]

```

RESET:
    SEI                      ; Interrupt disable
    CLD
    CLT
;
    LDX  #$FF                ; Set stack bottom
    TXS
;
    LDM  #%10000000,CPUM     ; Set CPU mode register
;
; Wait f(XIN) oscillation stabilizing time
;
    LDM  #%00000000,CPUM     ; Set CPU mode register
;
    LDA  #0
    LDX  #>RAM_top
RAM_clear: STA  $00,X
           INX
           BNE  RAM_clear
;
Sio_initial:
    LDM  #%11010000,SIOCON   ; BRG count source : f(Xin)
                                ; synchronous clock : divided 4
                                ; P1_3 function : normal I/O pin
                                ; interrupt request factor : transmit buffer is empty
                                ; enable transmit
                                ; disable receive
                                ; serial I/O mode : synchronous serial I/O mode
                                ; enable serial I/O
                                ; set baud rate
    LDM  #$07,BRG
    CLB  0,INTEDGE           ; INT0 falling edge active
    LDM  #$055,SEND_DATA
    LDM  #$0AA,SEND_DATA+1
;
;
;-----
__MAIN:
    BBC  2,IREQ1,__MAIN      ; input INT0 falling edge
    CLB  2,IREQ1
    LDA  SEND_DATA
    STA  TBRB                ; Send data write
__MAIN00:
    BBC  0,SIOSTS,__MAIN00   ; data send? -> no
;
    LDA  SEND_DATA+1
    STA  TBRB                ; Next send data write
__MAIN01:
    BBC  0,SIOSTS,__MAIN01   ; data send? -> no
;
__MAIN02:
    BBC  2,SIOSTS,__MAIN02   ; Shift end check ? -> no
;
    BRA  __MAIN
;

```

**Figure 7 Sample Programming Code (Transmit Side)**



# [Reset Start •• Main Routine Process]

```

RESET:
    SEI                      ; Interrupt disable
    CLD
    CLT
;
    LDX  #$FFF              ; Set stack bottom
    TXS
;
    LDM  #%10000000,CPUM    ; Set CPU mode register
;
; Wait f(XIN) oscillation stabilizing time
;
    LDM  #%00000000,CPUM    ; Set CPU mode register
;
    LDA  #0
    LDX  #>RAM_top
RAM_clear: STA  $00,X
    INX
    BNE  RAM_clear
;
Sio_initial:
    LDM  #%11110110,SIOCON  ; synchronous clock : external clock
                                ; P1_3 pin function : SRDY output pin
                                ; enable transmit
                                ; enable receive
                                ; serial I/O mode : synchronous serial I/O mode
                                ; enable serial I/O

    LDM  #$00,TCSS2         ; select timer 1 count source : f(Xin)/16
    LDM  #65-1,PRE1         ; Set Prescaler 1
    LDM  #8-1,T1            ; Set Timer 1
    CLB  5,IREQ2            ; clear timer 1 interrupt request
    NOP
;
; -----
__MAIN:
    BBC  5,IREQ2,__MAIN     ; 2ms?
    CLB  5,IREQ2

    LDA  #$00               ; write dummy data
    STA  TBRB

__MAIN_00:
    BBC  1,SIOSTS,__MAIN_00 ; data receive ? -> no
;
    LDA  TBRB
    STA  Receive_Data       ; store receive data

    LDA  #$00               ; write dummy data
    STA  TBRB

__MAIN01:
    BBC  1,SIOSTS,__MAIN01  ; data receive ? -> no
;
    LDA  TBRB
    STA  Receive_Data+1     ; store next receive data

    BRA  __MAIN
;

```

**Figure 8 Sample Programming Code (Receive Side)**

## 5. Reference

Data Sheet  
7544 Group Data sheet  
7544 Group Data sheet (QzROM Version)

Before using this manual, please visit our website to verify that this is the most updated document available.

Renesas Technology Corporation Semiconductor Home Page  
<http://www.renesas.com/en/740>

E-mail Support  
E-mail: [support\\_apl@renesas.com](mailto:support_apl@renesas.com)

REVISION HISTORY	7544 Group Clock Synchronous Serial I/O
------------------	---

Rev.	Date	Description	
		Page	Summary
1.00	Apr 01, 2003	-	First Edition issued
2.00	Nov 12, 2004	8-9	Sample Programming Code added.

### Keep safety first in your circuit designs!

1. Renesas Technology Corporation puts the maximum effort into making semiconductor products better and more reliable, but there is always the possibility that trouble may occur with them. Trouble with semiconductors may lead to personal injury, fire or property damage.  
Remember to give due consideration to safety when making your circuit designs, with appropriate measures such as (i) placement of substitutive, auxiliary circuits, (ii) use of nonflammable material or (iii) prevention against any malfunction or mishap.

### Notes regarding these materials

1. These materials are intended as a reference to assist our customers in the selection of the Renesas Technology Corporation product best suited to the customer's application; they do not convey any license under any intellectual property rights, or any other rights, belonging to Renesas Technology Corporation or a third party.
2. Renesas Technology Corporation assumes no responsibility for any damage, or infringement of any third-party's rights, originating in the use of any product data, diagrams, charts, programs, algorithms, or circuit application examples contained in these materials.
3. All information contained in these materials, including product data, diagrams, charts, programs and algorithms represents information on products at the time of publication of these materials, and are subject to change by Renesas Technology Corporation without notice due to product improvements or other reasons. It is therefore recommended that customers contact Renesas Technology Corporation or an authorized Renesas Technology Corporation product distributor for the latest product information before purchasing a product listed herein.  
The information described here may contain technical inaccuracies or typographical errors.  
Renesas Technology Corporation assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors.  
Please also pay attention to information published by Renesas Technology Corporation by various means, including the Renesas Technology Corporation Semiconductor home page (<http://www.renesas.com>).
4. When using any or all of the information contained in these materials, including product data, diagrams, charts, programs, and algorithms, please be sure to evaluate all information as a total system before making a final decision on the applicability of the information and products. Renesas Technology Corporation assumes no responsibility for any damage, liability or other loss resulting from the information contained herein.
5. Renesas Technology Corporation semiconductors are not designed or manufactured for use in a device or system that is used under circumstances in which human life is potentially at stake.  
Please contact Renesas Technology Corporation or an authorized Renesas Technology Corporation product distributor when considering the use of a product contained herein for any specific purposes, such as apparatus or systems for transportation, vehicular, medical, aerospace, nuclear, or undersea repeater use.
6. The prior written approval of Renesas Technology Corporation is necessary to reprint or reproduce in whole or in part these materials.
7. If these products or technologies are subject to the Japanese export control restrictions, they must be exported under a license from the Japanese government and cannot be imported into a country other than the approved destination.  
Any diversion or reexport contrary to the export control laws and regulations of Japan and/or the country of destination is prohibited.
8. Please contact Renesas Technology Corporation for further details on these materials or the products contained therein.