



Provides superior wetting performance for hand soldering.



275 No Clean Flux Cored Wire Solder

Characteristics: Colorless translucent residues. Eliminates cleaning; Low smoke and odor. 1lb. Spool. **Compliant Specs:** Telcordia Issue 1 GR-78 CORE + IPC/J-STD-004 Flux designator ROL0.

TT No.	Alloy	Diameter	Core Size	PRICE/ea.
488S01315	K100LD – A eutectic tin/copper alloy with controlled metallic dopants	.015"	66	\$35.57
488S01320		.020"	66	\$31.47
488S01325		.025"	66	\$24.92
488S01331		.031"	66	\$24.24
488S01350		.050"	66	\$21.84
488S01362		.062"	66	\$24.03
488S06808	Sn96.5 Ag3 Cu0.5	.015"	58	\$46.92
488S07863	Sn96.5 Ag3 Cu0.5	.020"	58	\$34.25
488S0617	Sn96.5 Ag3 Cu0.5	.025"	58	\$31.55
488S07871	Sn96.5 Ag3 Cu0.5	.031"	58	\$28.77
488S07866	Sn96.5 Ag3 Cu0.5	.050"	58	\$36.08
488S07867	Sn96.5 Ag3 Cu0.5	.062"	58	\$32.75